履带链节测漏加注压装设备

Chain Link Leak Detection, Filling & Assembly Device

1. 产品名称: 履带链节测漏加注压装设备

Product Name: Chain Link Leak Detection, Filling & Assembly Device

用途:自动检测链节气密性,气密合格后自动真空加注润滑油,最后压装打塞。

Application: Automatic testing of link leak, automatic vacuum filling of lubricant, and pressing cap.



履带链节测漏加注压装设备 Chain Link Leak Detection, Filling & Assembly Device

3. 主要功能和特点:

Functions and Specifications ●气密检测、自动真空加注、压装三部分机械部分独立,控制部 分集中

Independent mechanical stations including air leak testing, automatic vacuum filling and assembly, and centralized control function

●具备工件到位确认功能,不到位无法进行其他动作 Able to confirm work–piece in–place, and do not to conduct other operation if not in place

●工装可XY双向调整,适合多种工件

Tooling to be adjusted in X,Y directions, suitable for multiple work – pieces

●测试结果通过声光多点报警,防止人为忽略测试结果 Testing results indicate in multi points through acousto–optic means to prevent human negligence

4. 核心器件:FL-600M型气密检漏仪、MI-170型数字压力表 Key Device:FL-600 M Air Leak Tester, MI-170 Digital Manometer

5. 测试节拍:1.0min/件 Testing Rate: 1.0min/pcs



加注压装部分 Filling and assembly station

变速器输入轴气密测试检测设备 Transmission Input Shaft Leak Testing System

1. 产品名称:变速器输入轴气密测试检测设备

Product Name: Transmission Input Shaft Leak Testing System

2. 用途: 对变速器输入轴进行气密性检测

Application: leak testing of the transmission input shaft



输入轴气密测试检测设备 Input Shaft Leak Testing System

 主要功能和特点: Functions and Specifications
●声光报警功能
Audible and visual alarm function
操作简便,测试时间短
Simple operation, short testing time

4. 核心器件: FL-601气密检漏仪 Key Device: FL-601 Air Leak Tester

5. 测试节拍: 1.25min/件 Testing Rate: 1.25min/pcs



自动封堵(左侧部分)输入轴(右侧) Automatic plugging (on the left) Input Shaft (on the right)